

TUC 20

Универсальный рукав для минерального масла



Приложение:

Гибкий рукав, предназначен для транспортировке минерального масла и топлива с максимальным содержанием ароматических углеводородов 40% и сжатого воздуха. Многоцелевой шланг для различных областей применения в промышленности, строительстве и сельском хозяйстве.

Рабочая температура: -40 °C / +100 °C.

Коэффициент безопасности: 3 : 1

Внутренний слой: Синтетический каучук, черный, гладкий, антистатический, маслостойкий.

Усиление: Текстильная навивка.

Наружный слой: синтетический каучук, черный, гладкий, антистатический, устойчивый к истиранию, маслу и озону

Маркировка: Сплошная маркировка, белая: „SEMPERIT S TUC 20 Öl/Luft Oil/Air PN 20 bar Antistatic MADE IN EU“.

Особенности:

Дополнительные размеры по запросу.

Номер позиции	Внутр. Ø		Толщ. стенки. мм	Наружн Ø мм	Рабочее давлен. бар (max)	Кол-во вкладышей	Радиус изгиба мин. мм.	Вес кг/м	Длина бухты макс. м
	мм	Дюйм							
68112 0630	6,0	1/4	3,0	12,0	20	2	40	0,15	50
68112 0835	8,0	5/16	3,5	15,0	20	2	50	0,20	50
68112 1035	10,0	3/8	3,5	17,0	20	2	60	0,22	50
68112 1335	13,0	1/2	3,5	20,0	20	2	80	0,30	50
68112 1640	16,0	5/8	4,0	24,0	20	2	100	0,40	50
68112 1945	19,0	3/4	4,5	28,0	20	2	120	0,50	50
68112 2550	25,0	1	5,0	35,0	20	2	150	0,73	50
68112 3250	32,0	1 1/4	5,0	42,0	20	4	190	0,75	50
68112 3860	38,0	1 1/2	6,0	50,0	20	4	230	1,10	50

Please note: General information about our range of products can be found in the appendix to this catalogue. Before using with new or untested media, or before using in applications that are not covered in the product information, written advice must first be obtained from a specialist dealer or a Semperit application engineer. All products must be inspected regularly for operational safety. For safety reasons, hoses must be replaced in the event of damage, especially if the cover is damaged. All products must be stored and maintained according to our storage, care and maintenance instructions, and according to DIN 7716:1982.

We are constantly developing and improving our products for our customers. For the latest product information, please visit our website www.semperflex.com regularly or contact one of our specialist dealers or Semperit application engineers. Contracts are agreed according to our general terms and conditions. Subject to change without notice.

Important notice: This catalogue has been prepared with the greatest care in order to provide you with all the information you need. The information contained herein incorporates the latest state-of-the-art technology, and is the result of trials and tests carried out over many years, or conforms to the resistance requirements of the media listed as set out in ISO TR 7620:2005 (E). The individual conditions of use affect the use of each product. They therefore only ensure the safety that can be expected assuming that the specifications in our written product information, the specifications regarding resistance to chemicals and our cleaning procedures are all complied with. We cannot guarantee this level of safety in the event of improper handling, e.g. squashing, rupturing, stretching or filling with media that are not permitted. Unless specified otherwise, all hoses are manufactured to EN ISO 1307:2006.

Version: 09. 09. 2016

semperflex® 
INDUSTRIAL

A MEMBER OF THE SEMPERIT-GROUP

"

"

: (495) 642-42-72. e-mail: info@tdgidronika.ru. www.tdgidronika.ru